

# X-TYPE PLUS

## THE PERFECT MIDDLE-CLASS-COMPLEMENT FOR YOUR MACHINERY



- + Minor need of space**
  - > Perfect for smaller production halls as a result of her small diameter
- + Adjustable screen holders for various frame sizes**
  - > Simple usage of different screen lock systems
- + Adjustable index speed control (optional)**
  - > Perfectly adaptable for every job speed
- + MHM Rollerframe screen holding system**
  - > High resiliency leads to a very good printing result
- + Individual off-contact adjustment on all stations**
  - > Off-contact can be set separately for each station > maximum flexibility
- + Multiprint-function (optional)**
  - > Maximum printing flexibility



# X-TYPE PLUS



### Specifications (all models)

|  |   |
|--|---|
| Machine height                             | 180 cm / 71 "   |
| Max. print area                            | 43 x 50 cm / 16 x 19 "                                |
| Min. air pressure                          | 7 bar / 101,5 psi (filtered, dry air supply only)     |
| Drive system                               | AC inverter indexer motor / electrical squeegee drive |
| Electrical supply                          | 1 ph ~200 - 240 V, 50 / 60 Hz (+/- 5 %)               |
| Electrical requirement (indexer)           | 1,6 kW  |
| Electrical requirement (per print station) | 0,4 kW  |
| Registration accuracy                      | +/- 0,02 mm / +/- 0.00079 "                           |
| Rec. frame profile                         | 4 x 4 cm / 1.57 x 1.57 "                              |
| Max. frame size                            | 60 x 84 cm / 23,6 x 33,1 "                            |
| Max. production capacity                   | 1.000 - 1.200 pcs. / h (according to model)           |

### Specifications (per model)

|                               | SPXC 08               | SPXC 10               |
|-------------------------------|-----------------------|-----------------------|
| Number of pallets             | 8                     | 10                    |
| Max. number of print stations | 6                     | 8                     |
| Max. diameter                 | 370 cm / 146 "        | 410 cm / 162 "        |
| Machine weight (kg / lbs)     | 1.100 / 2,425         | 1.270 / 2,800         |
| Average air consumption       | 220 l / min (7.8 cfm) | 280 l / min (9.9 cfm) |
| Rec. air supply               | 350 l / min           | 400 l / min           |

