

S-TYPE XTREME

RAISE YOUR PRODUCTIVITY TO THE NEXT LEVEL!



- + **Squeegee arm lift for increased visibility**
> Simple screen adjustment and -cleaning, increased productivity
- + **Squeegee pressure regulator on every station**
> Specific adjustments for all print jobs
- + **Independent flood / print speed controls**
> Simple, specific setting for every print job
- + **Flash cure adjustments from main control unit**
> Simple control via a centralised control point
- + **Tool-free front / rear stroke length adjustment**
> Fast and time-saving adjustments
- + **Full micro-registration with zero starting position**
> Time-saving during print preparation



S-TYPE XTREME



Specifications (all models)

Machine height	175 cm / 68.9 "
Min. air pressure	7 bar / 101.5 psi (filtered, dry air supply only)
Drive system	AC-Servo drive indexer / electrical squeegee drive
Electrical supply	1 ph ~200 - 240 V, 50 / 60 Hz (+/- 5 %)
Electrical requirement (indexer)	2 kW
Electrical requirement (per print station)	0.4 kW
Registration accuracy	+/- 0,02 mm / +/- 0.00079 "
Rec. frame profile	4 x 4 cm / 1.57 x 1.57 "
Max. frame size 43 x 50 cm	84 x 60 cm / 33.1 x 23.6 "
Max. frame size 45 x 55 cm	100 x 66 cm / 39.4 x 26 "
Max. frame size 45 x 70 cm	115 x 66 cm / 45.3 x 26 "
Max. frame size 50 x 70 cm	112 x 75 cm / 44.1 x 29.5 "
Max. production capacity (pieces / h)	1.100 - 1.400 / 1,100 - 1,400 (acc. to model)

Specifications (per model)

	SPSX-08	SPSX-10	SPSX-12	SPSX-14	SPSX-16	SPSX-18
Number of pallets	8	10	12	14	16	18
Max. number of print stations	6	8	10	12	14	16
Max. diameter 43 x 50 cm / 16.9 x 19.7 "	385 cm / 152 "	420 cm / 165 "	450 cm / 177 "	490 cm / 193 "	528 cm / 208 "	570 cm / 224 "
Max. diameter 45 x 55 cm / 17.7 x 25.6 "	415 cm / 163 "	455 cm / 179 "	500 cm / 197 "	542 cm / 213 "	584 cm / 230 "	625 cm / 246 "
Max. diameter 45 x 70 cm / 17.7 x 27.6 "	n/A	n/A	n/A	n/A	614 cm / 241 "	n/A
Max. diameter 50 x 70 cm / 19.7 x 31.5 "	460 cm / 181 "	505 cm / 199 "	550 cm / 217 "	595 cm / 234 "	n/A	n/A
Machine weight (kg / lbs)	1,450 / 3,200	1,680 / 3,700	1,900 / 4,190	2,100 / 4,630	2,650 / 5,840	2,870 / 6,330
Average air consumption (l/min)	220 (7.8 cfm)	280 (9.9 cfm)	340 (12.0 cfm)	400 (14.1 cfm)	460 (16.2 cfm)	520 (18.4 cfm)
Rec. air supply (l/min)	350 (12.4 cfm)	400 (14.1 cfm)	450 (15.9 cfm)	500 (17.7 cfm)	600 (21.2 cfm)	650 (23 cfm)

